

INCOMPARABLE DEEP CYCLE AGM BATTERY

LDC12-55 (12V55Ah)




CHARACTERISTICS


Item		Specifications
Voltage		12V
Dimension	Length	223mm (8.78inches)
	Width	123mm (4.84inches)
	Container Height	175mm (6.89inches)
	Total Height	175mm (6.89inches)
Approx Weight		13.4kg (29.5lbs)
Terminal		T12-A(M6)
Container Material		ABS
Capacity	20HR	55Ah
	5HR	48Ah
Operating Temp. Range	Discharge	-20~55°C (-4~131°F)
	Charge	0~40°C (32~104°F)
	Storage	-15~40°C (5~104°F)

APPLICATIONS

- Electric vehicle
- Golf cart
- Sightseeing
- Cleaning equipment
- AWP
- Mobility



Note: Terminal Torque Values in-lb(Nm):34.52-47.79(3.9-5.4)



INCOMPARABLE DEEP CYCLE AGM BATTERY

LDC12-55 (12V55Ah)

GENERAL FEATURES

Stable initial capacity

- PAM/NAM amount optimization
- 4BS crystal paste mixing & curing technology
- Double layer separator technology
- Improved design electrolyte S.G.

Less water loss

- PAM/NAM amount optimization
- New PAM/NAM recipe introduced
- Rare earth alloy

Solve NAM sulphation

- Carbon boost technology
- Pre-sulfate technology

Improved PSoC cycling

- Carbon boost technology
- Mix carbon boost technology
- Targeting for higher level through carbon technology

Delay PAM softening and shedding

- Plate assembly pressure re-engineering
- 4BS crystal paste mixing & curing technology
- Higher paste density


Optimize electrolyte stratification

- Introduce AGM-GEL technology


Excellent deep cycle performance

- Plate assembly pressure re-engineering
- New PAM/NAM recipe introduced
- Gel electrolyte technology
- Rare earth alloy
- Double layer separator technology
- Lower acid filling temperature


Charging Profiles



Relationship of OCV and State Of Charge



Cycle Life in Relation to Depth Of Discharges



Self-discharge Characteristics

