

LPGS SERIES-TRUE Hybrid GEL Battery

LPGS12-90(12V90AH)

Specification

Nominal Voltage	12V	
Nominal Capacity(10HR)	90.0AH	
Dimensions	Length	306±3mm (12.05 inches)
	Width	168±2mm (6.61 inches)
	Container Height	208±3mm (8.19 inches)
	Total Height (with Terminal)	214±3mm (8.43 inches)
Approx Weight	Approx 26.8 kg (59.1lbs)	
Terminal	T6	
Container Material	ABS	
Rated Capacity	92.8 AH/4.64A	(20hr, 1.80V/cell, 25°C/77°F)
	90.0AH/9.0A	(10hr, 1.80V/cell, 25°C/77°F)
	76.5 AH/15.3A	(5hr, 1.75V/cell, 25°C/77°F)
	66.3AH/22.1A	(3hr, 1.75V/cell, 25°C/77°F)
	53.7 AH/53.7A	(1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	1080A (5s)	
Internal Resistance	Approx 5.5mΩ	
Operating Temp. Range	Discharge	-15~50°C (5~122°F)
	Charge	0~40°C (32~104°F)
	Storage	-15~40°C (5~104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than 27.0A. Voltage	
	14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage	
	13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	Leoch LPGS series batteries may be stored for up to 9 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Applications

- ◆ All purpose
- ◆ Uninterruptable Power Supply (UPS)
- ◆ Electric Power System (EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and security system
- ◆ Electronic apparatus and equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto control system

Constant Current Discharge (Amperes) at 25 °C (77°F)




F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	145.1	114.1	97.0	81.2	64.1	48.7	40.3	25.7	19.9	16.4	13.9	12.2	9.90	8.35	4.50
1.80V/cell	192.0	143.6	115.5	94.5	73.8	55.3	44.8	27.8	21.4	17.5	14.9	13.0	10.5	9.00	4.64
1.75V/cell	220.9	161.1	128.8	103.8	78.7	58.4	47.4	29.2	22.1	18.0	15.3	13.3	10.7	9.09	4.68
1.70V/cell	246.1	177.7	139.1	110.3	83.0	61.4	49.5	30.6	23.0	18.5	15.8	13.7	10.8	9.18	4.77
1.65V/cell	268.7	189.8	146.4	116.1	86.9	63.2	51.3	31.4	23.8	19.1	16.1	14.0	11.0	9.27	4.82
1.60V/cell	298.8	207.8	158.0	124.7	92.3	66.9	53.7	32.6	24.6	19.5	16.4	14.2	11.2	9.36	4.86

Constant Power Discharge (Watts/cell) at 25 °C (77°F)


F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	267.3	212.3	182.4	154.1	122.9	94.1	78.1	49.9	38.9	32.1	27.4	23.9	19.5	16.6	8.95
1.80V/cell	350.1	264.4	214.5	177.0	139.7	105.9	86.4	53.9	41.6	34.0	29.3	25.6	20.8	17.8	9.18
1.75V/cell	394.0	291.6	236.0	192.3	147.6	111.1	91.0	56.3	42.9	35.0	29.9	26.2	21.1	18.0	9.27
1.70V/cell	426.2	313.7	250.9	202.7	154.6	116.0	94.5	59.0	44.3	36.0	30.6	26.6	21.3	18.1	9.45
1.65V/cell	457.9	331.6	261.6	211.2	160.4	118.5	97.3	60.2	45.8	36.9	31.2	27.2	21.6	18.3	9.54
1.60V/cell	497.3	354.7	277.5	224.4	169.0	124.5	101.4	62.1	47.2	37.6	31.7	27.7	21.9	18.5	9.63

Dimensions


T6 Terminal




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



General Relation of Capacity VS. Storage Time



Sales Office

China sales office:

Add: 5th Floor, Xinbaohui Bldg., Nanshai Blvd., Nanshan, Shenzhen, China. 518052
 Tel: +86-755-86036060 (100 lines)
 Fax: +86-755-26067269
 E-mail: export@leoch.com
 Http: www.leoch.com

HongKong sales office:

Add: Workshop C, 33/F, TML Tower, No. 3 Hoi Shing Road, Tsuen Wan, New Territories, Hong Kong
 Tel: +852 35786666
 Fax: +852 21170016
 E-mail: sales.hk@leoch.com

Singapore sales office:

Add: No. 1 Tech Park Crescent, Singapore 638131
 Tel: +65 68416629
 Fax: +65 68443210
 Email: sales.sg@Leoch.com

North America sales office:

Add: 19751 Descartes, Unit A, Foothill Ranch, CA 92610, USA
 Tel: 949-588-5853
 Fax: 949-588-5966
 E-mail: sales@leoch.us
 Http: www.leoch.com

Europe sales office:

Add: 9B Wheatstone Court, Waterwells Business Park, Gloucester, GL2-2AQ, UK United Kingdom
 Tel: +44(0) 1452 729428 / 1452 729696
 Fax: +44 (0)1452-690125
 E-mail: Sales.Europe@leoch.com