AGM START-STOP BATTERY

AGM34-55 (12V55Ah)





CHARACTERISTICS


| Item | | Specifications |
|--------------------------------|--------|--------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity (20HR) | | 55Ah |
| Reserve Capacity | | 120min |
| Cold Cranking Amps@0°F (-18°C) | | 650A |
| | Length | 276mm (10.9inches) |
| Dimension | Width | 168mm (6.61inches) |
| | Height | 196mm (7.72inches) |
| Approx Weight | | 19.1kg (42.1lbs) |
| Terminal | | 1 |
| Cell layout | | 1 |
| Hold-Down | | B1 |
| Case | | Black-PP Material |
| Cover | | Black-PP Material |
| Handle | | TS4 |


APPLICATIONS

- ·Car with start-stop system
- •EV/HEV
- •Engine start


GENERAL FEATURES

- •Maximum CCA and life
- Valve regulated technology
- •Advanced Absorbed Glass Mat (AGM) technology
- •Top-level safety absolutely no free acid
- •2x Faster Charge Acceptance than conventional starter batteries
- •3x higher cycle life than conventional starter batteries
- •Suit for working in partial state of charge operations (PSoC)
- •OE quality certification









Leoch International Technology Ltd.

www.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.

^{*}Values are subject to variation of +/- 5% in normal manufacturing processes.