AGM START-STOP BATTERY

AGM-L4 (12V80Ah)





CHARACTERISTICS

| Item | | Specifications |
|--------------------------------|------------------------------|--------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity (20HR) | | 80Ah |
| Reserve Capacity | | 140min |
| Cold Cranking Amps@0°F (-18°C) | | 800A |
| Dimension | Length | 315mm (12.4inches) |
| | Width | 175mm (6.89inches) |
| | Container Height | 190mm (7.48inches) |
| | Total Height (with Terminal) | 190mm (7.48inches) |
| Approx Weight | | 23.3kg (51.4lbs) |
| Terminal | | 1 |
| Cell layout | | 0 |
| Hold-Down | | B13 |
| Case | | Black-PP Material |
| Cover | | Black-PP Material |
| Handle | | TS6 |

APPLICATIONS

- ·Car with start-stop system
- •EV/HEV
- Engine start

Ø<u>19. 5-0.</u>3 Ø17. 9-0.

Leoch International Technology Ltd.


www.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

GENERAL FEATURES

- •Maximum CCA and life
- ·Valve regulated technology
- ·Advanced Absorbed Glass Mat (AGM) technology
- •Top-level safety absolutely no free acid
- •2x Faster Charge Acceptance than conventional starter batteries
- •3x higher cycle life than conventional starter batteries
- •Suit for working in partial state of charge operations (PSoC)
- •OE quality certification



Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.

mww.leoch.eu

^{*}Values are subject to variation of +/- 5% in normal manufacturing processes.