AUXILIARY BATTERY MB14-4 (12V14Ah)





CHARACTERISTICS

| Item | | Specifications |
|--------------------------------|--------|--------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity (20HR) | | 14Ah |
| Cold Cranking Amps@0°F (-18°C) | | 210A |
| Dimension | Length | 150mm (5.91inches) |
| | Width | 87mm (3.43inches) |
| | Height | 145mm (5.71inches) |
| Approx Weight | | 4.80kg (10.6lbs) |
| Terminal | | M |
| Cell layout | | 1 |
| Hold-Down | | B0 |
| Case | | Black-PP Material |
| Cover | | Black-PP Material |
| Handle | | / |

APPLICATIONS

•High-end car auxiliary

•Safety assistant








*Values are subject to variation of +/- 5% in normal manufacturing processes.


Leoch International Technology Ltd.


Leoch Batteries Pte Ltd

GENERAL FEATURES

- •VRLA technology with long life
- •Modified PP material case and cover, with high strength and impact resistance
- •Top-level safety absolutely no free acid
- •Absorb the instantaneous overvoltage in the vehicle circuit, protect the vehicle circuit from damage
- •Uninterruptible power supply for safety components and escort for safety during driving
- •OE quality certification







Leoch Battery Corporation @ www.leochamericas.com Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-MB14-4-PD-EN-V1.0-20250103