## **FLOODED BATTERY** 65-670 (12V80Ah)





## **CHARACTERISTICS**


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		80Ah
Reserve Capacity		138min
Cold Cranking Amps@0°F (-18°C)		670A
	Length	298mm (11.7inches)
Dimension	Width	190mm (7.48inches)
	Height	192mm (7.56inches)
Approx Weight		21.1kg (46.5lbs)
Terminal		1
Cell layout		1
Hold-Down		B01
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS4

## **APPLICATIONS**


•Car start

•EV/HEV

•Engine start



POS



 $18\pm$ 

**GENERAL FEATURES** 


•High capacity and high CCA


Long life


- •Advanced lead-calcium alloy technology, maintenance-free design
- •Patented venting system bring less water loss and prevent acid

leakage

•OE quality certification







\*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd. www.leoch.com

Leoch Batteries Pte Ltd www.leoch.sg

Leoch Battery Corporation www.leochamericas.com

Leoch Europe S.A. @ www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-65-670-PD-EN-V1.0-20241230