



LEOCH BATTERY

BCI 58R-520 (12V55Ah)



Physical Specification (mm)

| | | |
|------------------------|-----------------------------|-------------------------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity(20HR) | | 55Ah |
| Dimension | Length | 240±2mm(9.45inches) |
| | Width | 174±2mm(6.85inches) |
| | Container Height | 157±2mm(6.18inches) |
| | Total Height(with Terminal) | 177±2mm(6.97inches) |
| Weight | | Approx 13.4Kg(29.55lbs) |
| Acid | | 1.280±0.015g/cm ³ (25°C) |
| Standard Terminal | | 1 |
| Cell layout | | 0 |
| Hold-Down | | B01 |
| Cell plate qty | | / |
| Case | | Black-PP Material |
| Cover | | Black-PP Material |
| Handle | | Black-PP Material |
| QTY/PLT/layer | | / |


Standard Terminal (mm) Cell Layout

| Terminal Type | D | |
|---------------|-----------------------------------|-----------------------------------|
| | Positive | Negative |
| 1 | 19.5 ⁰ _{-0.3} | 17.9 ⁰ _{-0.3} |

Figure(0)

*Values are subject to variation of +/- 5% in normal manufacturing processes.
 *Technical specifications and the product line above could be changed without prior notice.


Dimensions (mm)



Electrical Specification

| | | |
|---|---------------------|-------|
| Rated Capacity | 20 hour rate(2.75A) | 55Ah |
| Reserve Capacity | | 88min |
| Cold Cranking Performance Amps@0°F(-18°C) | | 520A |

Discharge Characteristics(25°C,70°F)



Discharge Characteristics(-18°C,0°F)

