

FLOODED BATTERY

54513 (12V45Ah)



CHARACTERISTICS



Item	Specifications
Nominal Voltage	12V
Nominal Capacity (20HR)	45Ah
Reserve Capacity	70min
Cold Cranking Amps@0°F (-18°C)	430A
Dimension	Length 242mm(9.53inches)
	Width 175mm(6.89inches)
	Height 175mm(6.89inches)
Approx Weight	12.7kg(28.0lbs)
Terminal	1
Cell layout	0
Hold-Down	B13
Case	Black-PP Material
Cover	Black-PP Material
Handle	TS2

APPLICATIONS

- Car start
- EV/HEV
- Engine start

GENERAL FEATURES

- High capacity and high CCA
- Long life
- Advanced lead-calcium alloy technology, maintenance-free design
- Patented venting system bring less water loss and prevent acid leakage
- OE quality certification



*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.

www.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.

www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation.
© LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted. Subject to revisions without prior notice. E&OE.

Publication No.: LB-54513-PD-EN-V1.0-20250220