## **FLOODED BATTERY** 55453 (12V54Ah)





## **CHARACTERISTICS**

| Item                           |        | Specifications     |
|--------------------------------|--------|--------------------|
| Nominal Voltage                |        | 12V                |
| Nominal Capacity (20HR)        |        | 54Ah               |
| Reserve Capacity               |        | 87min              |
| Cold Cranking Amps@0°F (-18°C) |        | 470A               |
|                                | Length | 278mm (10.9inches) |
| Dimension                      | Width  | 175mm (6.89inches) |
|                                | Height | 190mm (7.48inches) |
| Approx Weight                  |        | 15.5kg (34.2lbs)   |
| Terminal                       |        | 1                  |
| Cell layout                    |        | 0                  |
| Hold-Down                      |        | B13                |
| Case                           |        | Black-PP Material  |
| Cover                          |        | Black-PP Material  |
| Handle                         |        | TS6                |

## **APPLICATIONS**

•Car start

•EV/HEV

•Engine start




•High capacity and high CCA

Long life

- •Advanced lead-calcium alloy technology, maintenance-free design
- •Patented venting system bring less water loss and prevent acid

leakage


•OE quality certification




\*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.


@ www.leoch.com



NEG









Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved.Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Leoch Batteries Pte Ltd

www.leoch.sg

Publication No.:LB-55453-PD-EN-V1.0-20241228