FLOODED BATTERY 58015 (12V80Ah)





CHARACTERISTICS

Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		80Ah
Reserve Capacity		138min
Cold Cranking Amps@0°F (-18°C)		650A
	Length	351mm (13.8inches)
Dimension	Width	174mm (6.85inches)
	Height	173mm (6.81inches)
Approx Weight		20.2kg (44.5lbs)
Terminal		1
Cell layout		0
Hold-Down		B13
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS6

APPLICATIONS

•Car start

•EV/HEV

•Engine start




•High capacity and high CCA

Long life


- •Advanced lead-calcium alloy technology, maintenance-free design
- •Patented venting system bring less water loss and prevent acid


leakage


•OE quality certification



*Values are subject to variation of +/- 5% in normal manufacturing processes.







Leoch International Technology Ltd.

Leoch Batteries Pte Ltd

Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved.Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-58015-PD-EN-V1.1-20250217