FLOODED BATTERY 58043 (12V80Ah)





CHARACTERISTICS


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		80Ah
Reserve Capacity		138min
Cold Cranking Amps@0°F (-18°C)		650A
	Length	314mm (12.4inches)
Dimension	Width	174mm (6.85inches)
	Height	190mm (7.48inches)
Approx Weight		19.7kg (43.4lbs)
Terminal		1
Cell layout		0
Hold-Down		B13
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS6

APPLICATIONS

Car start

•EV/HEV

•Engine start



GENERAL FEATURES


·High capacity and high CCA


Long life


- •Advanced lead-calcium alloy technology, maintenance-free design
- •Patented venting system bring less water loss and prevent acid

leakage


•OE quality certification











*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd. @ www.leoch.com

Leoch Batteries Pte Ltd www.leoch.sg

Leoch Battery Corporation www.leochamericas.com

Leoch Europe S.A. @ www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-58043-PD-EN-V1.0-20241228