FLOODED BATTERY

61042 (12V110Ah)





CHARACTERISTICS


| Item | | Specifications |
|--------------------------------|--------|--------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity (20HR) | | 110Ah |
| Reserve Capacity | | 201min |
| Cold Cranking Amps@0°F (-18°C) | | 850A |
| | Length | 394mm (15.5inches) |
| Dimension | Width | 175mm (6.89inches) |
| | Height | 190mm (7.48inches) |
| Approx Weight | | 25.5kg (56.2lbs) |
| Terminal | | 1 |
| Cell layout | | 0 |
| Hold-Down | | B13 |
| Case | | Black-PP Material |
| Cover | | Black-PP Material |
| Handle | | TS6 |
| | | |


APPLICATIONS

- Car start
- •EV/HEV
- •Engine start

GENERAL FEATURES

- ·High capacity and high CCA
- Long life
- •Advanced lead-calcium alloy technology, maintenance-free design
- •Patented venting system bring less water loss and prevent acid leakage
- •OE quality certification





Leoch International Technology Ltd.

mww.leoch.com

Leoch Batteries Pte Ltd

⊕ www.leoch.sg
⊕ www.

Leoch Battery Corporation

@ www.leochamericas.com

Leoch Europe S.A.



^{*}Values are subject to variation of +/- 5% in normal manufacturing processes.