FLOODED HIGH TEMPERATURE BATTERY

110D31LHT (12V95Ah)





CHARACTERISTICS


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		95Ah
Reserve Capacity		169min
Cold Cranking Amps@0°F (-18°C)		640A
	Length	303mm (11.9inches)
Dimension	Width	170mm (6.69inches)
	Height	222mm (8.74inches)
Approx Weight		21.8kg (48.1lbs)
Terminal		1
Cell layout		0
Hold-Down		B1
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS1


APPLICATIONS


- Car start
- •EV/HEV
- •Engine start

Ø<u>17.</u>9-0. ϕ 19. 5-0. NEG

- •Design for high temperature countries and regions
- ·Superior life in high temperature environment
- ·High tin alloy and thicker positive grid
- ·High-temp paste
- ·Patented venting system bring less water loss and prevent acid leakage







Leoch International Technology Ltd.

mww.leoch.com

Leoch Batteries Pte Ltd

mww.leoch.sg

Leoch Battery Corporation

mww.leochamericas.com

Leoch Europe S.A.

mww.leoch.eu

GENERAL FEATURES

^{*}Values are subject to variation of +/- 5% in normal manufacturing processes.