

FLOODED HIGH TEMPERATURE BATTERY

175G51RHT (12V175Ah)



CHARACTERISTICS



Item	Specifications
Nominal Voltage	12V
Nominal Capacity (20HR)	175Ah
Reserve Capacity	348min
Cold Cranking Amps@0°F (-18°C)	1050A
Dimension	Length
	510mm(20.1inches)
	Width
Height	222mm(8.74inches)
	217mm(8.54inches)
Approx Weight	42.9kg(94.6lbs)
Terminal	1
Cell layout	3
Hold-Down	B0
Case	Black-PP Material
Cover	Black-PP Material
Handle	TS8

APPLICATIONS

- Car start
- EV/HEV
- Engine start

GENERAL FEATURES

- Design for high temperature countries and regions
- Superior life in high temperature environment
- High tin alloy and thicker positive grid
- High-temp paste
- Patented venting system bring less water loss and prevent acid leakage



*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.



Leoch Batteries Pte Ltd



Leoch Battery Corporation



Leoch Europe S.A.



Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation.
© LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted. Subject to revisions without prior notice. E&OE.

Publication No.: LB-175G51RHT-PD-EN-V1.0-20250220