## FLOODED HIGH TEMPERATURE BATTERY

36B20LHT (12V32Ah)





## **CHARACTERISTICS**


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		32Ah
Reserve Capacity		47min
Cold Cranking Amps@0°F (-18°C)		260A
	Length	195mm (7.68inches)
Dimension	Width	126mm (4.96inches)
	Height	222mm (8.74inches)
Approx Weight		9.1kg (20.1lbs)
Terminal		3
Cell layout		0
Hold-Down		В0
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS1

## **APPLICATIONS**


- ·Car start
- •EV/HEV
- •Engine start

## **GENERAL FEATURES**

- •Design for high temperature countries and regions
- •Superior life in high temperature environment
- ·High tin alloy and thicker positive grid
- ·High-temp paste
- Patented venting system bring less water loss and prevent acid leakage



<sup>201±2</sup> 202±2



Leoch International Technology Ltd.

mww.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

⊕ www.leochamericas.com

Leoch Europe S.A.



<sup>\*</sup>Values are subject to variation of +/- 5% in normal manufacturing processes.