FLOODED HIGH TEMPERATURE BATTERY

38B20LHT (12V36Ah)





CHARACTERISTICS


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		36Ah
Reserve Capacity		54mir
Cold Cranking Amps@0°F (-18°C)		300A
	Length	195mm (7.68inches)
Dimension	Width	126mm (4.96inches)
	Height	222mm (8.74inches)
Approx Weight		9.6kg (21.2lbs)
Terminal		3
Cell layout		0
Hold-Down		B0
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS1
Approx Weig Terminal Cell layout Hold-Down Case Cover	Width Height	126mm (4.96inche 222mm (8.74inche 9.6kg (21.2lb Black-PP Mater Black-PP Mater


APPLICATIONS


- ·Car start
- •EV/HEV
- •Engine start

\emptyset 14. $7^{0}_{-0.3}$ $\emptyset 13.0_{-0.3}^{0}$ POS NEG

- •Design for high temperature countries and regions
- •Superior life in high temperature environment
- ·High tin alloy and thicker positive grid
- ·High-temp paste
- ·Patented venting system bring less water loss and prevent acid leakage







Leoch International Technology Ltd.

mww.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

Leoch Europe S.A. mww.leochamericas.com



GENERAL FEATURES

^{*}Values are subject to variation of +/- 5% in normal manufacturing processes.