# FLOODED HIGH TEMPERATURE BATTERY

54025HT (12V40Ah)





# **CHARACTERISTICS**

Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		40Ah
Reserve Capacity		61mir
Cold Cranking Amps@0°F (-18°C)		350A
	Length	206mm(8.11inches)
Dimension	Width	174mm(6.85inches)
	Height	173mm(6.81inches)
Approx Weight		11.2kg(24.7lbs)
Terminal		1
Cell layout		0
Hold-Down		B13
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS2


### **APPLICATIONS**

- Car start
- •EV/HEV
- •Engine start


# Ø 19. 5\_0, 3 Ø 17. 9\_0. 3 Ø 17. 9\_0. 3 Ø 17. 9\_0. 8

# **GENERAL FEATURES**

- •Design for high temperature countries and regions
- •Superior life in high temperature environment
- ·High tin alloy and thicker positive grid
- ·High-temp paste
- Patented venting system bring less water loss and prevent acid leakage







Leoch International Technology Ltd.

@ www.leoch.com

www.leoch.sg

**Leoch Batteries Pte Ltd** 

Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.



<sup>\*</sup>Values are subject to variation of +/- 5% in normal manufacturing processes.