FLOODED HIGH TEMPERATURE BATTERY

54459HT (12V44Ah)





CHARACTERISTICS


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		44Ah
Reserve Capacity		68min
Cold Cranking Amps@0°F (-18°C)		350A
	Length	207mm (8.15inches)
Dimension	Width	175mm (6.89inches)
	Height	190mm (7.48inches)
Approx Weight		12.1kg (26.7lbs)
Terminal		1
Cell layout		0
Hold-Down		B13
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS2

APPLICATIONS

•Car start

•EV/HEV

•Engine start



*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.


Leoch Batteries Pte Ltd


Design for high temperature countries and regions
Superior life in high temperature environment


GENERAL FEATURES

•High tin alloy and thicker positive grid

- High-temp paste
- •Patented venting system bring less water loss and prevent acid leakage







Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-54459HT-PD-EN-V1.0-20250103