FLOODED HIGH TEMPERATURE BATTERY

56545HT (12V65Ah)






CHARACTERISTICS

Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		65Ah
Reserve Capacity		108min
Cold Cranking Amps@0°F (-18°C)		480A
Dimension	Length	278mm (10.9inches)
	Width	175mm (6.89inches)
	Height	190mm (7.48inches)
Approx Weight		16.4kg (36.2lbs)
Terminal		1
Cell layout		0
Hold-Down		B13
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS6

APPLICATIONS

- •Car start
- •EV/HEV


•Engine start



*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.

Leoch Batteries Pte Ltd



GENERAL FEATURES

•High tin alloy and thicker positive grid


•High-temp paste


leakage

·Design for high temperature countries and regions

•Patented venting system bring less water loss and prevent acid

·Superior life in high temperature environment





Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-56545HT-PD-EN-V1.0-20250103