HEAVY DUTY FLOODED BATTERY 160G51R (12V160Ah)






CHARACTERISTICS

Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		160Ah
Reserve Capacity		313min
Cold Cranking Amps@0°F (-18°C)		950A
	Length	510mm (20.1inches)
Dimension	Width	222mm (8.74inches)
	Height	217mm (8.54inches)
Approx Weight		40.3kg (88.8lbs)
Terminal		1
Cell layout		3
Hold-Down		B0
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS8

APPLICATIONS


•Commercial vehicle start


•Engine start



GENERAL FEATURES

- •High capacity and high CCA
- Maintenance-free
- High vibration resistance
- •Strong lead-calcium alloy grids for great corrosion resistance
- •High strength PP case and cover no need be worried about breakage
- OE quality certification





Leoch Battery Corporation

Leoch Europe S.A.

*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.

Leoch Batteries Pte Ltd

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-160G51R-PD-EN-V1.0-20250104