HEAVY DUTY FLOODED BATTERY 170G51R (12V170Ah)






CHARACTERISTICS

| Item | | Specifications |
|--------------------------------|--------|--------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity (20HR) | | 170Ah |
| Reserve Capacity | | 336min |
| Cold Cranking Amps@0°F (-18°C) | | 1000A |
| | Length | 510mm (20.1inches) |
| Dimension | Width | 222mm (8.74inches) |
| | Height | 217mm (8.54inches) |
| Approx Weight | | 41.8kg (92.2lbs) |
| Terminal | | 1 |
| Cell layout | | 3 |
| Hold-Down | | B0 |
| Case | | Black-PP Material |
| Cover | | Black-PP Material |
| Handle | | TS8 |

APPLICATIONS

·Commercial vehicle start

•Engine start





POS



GENERAL FEATURES

- •High capacity and high CCA
- Maintenance-free
- •High vibration resistance
- •Strong lead-calcium alloy grids for great corrosion resistance
- ·High strength PP case and cover no need be worried about breakage
- •OE quality certification







*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd. www.leoch.com

Leoch Batteries Pte Ltd www.leoch.sg

Leoch Battery Corporation @ www.leochamericas.com

Leoch Europe S.A. @ www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved.Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-170G51R-PD-EN-V1.0-20250104