FLOODED BATTERY 36B20L (12V32Ah)





CHARACTERISTICS


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		32Ah
Reserve Capacity		47min
Cold Cranking Amps@0°F (-18°C)		310A
	Length	195mm (7.68inches)
Dimension	Width	126mm (4.96inches)
	Height	222mm (8.74inches)
Approx Weight		9.2kg (20.3lbs)
Terminal		3
Cell layout		0
Hold-Down		B0
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS1

APPLICATIONS

•Car start

•EV/HEV

•Engine start









NEG

*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.

Leoch Batteries Pte Ltd

GENERAL FEATURES

•High capacity and high CCA


Long life


•Advanced lead-calcium alloy technology, maintenance-free design


•Patented venting system bring less water loss and prevent acid

leakage

OE quality certification







Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted. Subject to revisions without prior notice. E&OE.

Publication No.:LB-36B20L-PD-EN-V1.0-20241228