FLOODED BATTERY 46B24RS (12V45Ah)





CHARACTERISTICS


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		45Ah
Reserve Capacity		70min
Cold Cranking Amps@0°F (-18°C)		410A
	Length	236mm (9.29inches)
Dimension	Width	128mm (5.04inches)
	Height	222mm (8.74inches)
Approx Weight		11.7kg (25.8lbs)
Terminal		1
Cell layout		1
Hold-Down		B0
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS1
Handle		TS1


APPLICATIONS

•Car start

•EV/HEV

•Engine start









NEG

*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.

Leoch Batteries Pte Ltd




•High capacity and high CCA

Long life


- •Advanced lead-calcium alloy technology, maintenance-free design
- •Patented venting system bring less water loss and prevent acid

leakage

•OE quality certification







Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted. Subject to revisions without prior notice. E&OE.

Publication No.:LB-46B24RS-PD-EN-V1.0-20241228