FLOODED BATTERY

50D26R (12V55Ah)





CHARACTERISTICS


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		55Ah
Reserve Capacity		88min
Cold Cranking Amps@0°F (-18°C)		450A
	Length	259mm (10.2inches)
Dimension	Width	174.8mm (6.88inches)
	Height	221mm (8.70inches)
Approx Weight		16.1kg (35.5lbs)
Terminal		1
Cell layout		1
Hold-Down		B1
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS1

APPLICATIONS

- Car start
- •EV/HEV
- •Engine start

Ø19. 5-0.3 **Ø17.** 9-<u>0.</u> з P0S NEG

- ·High capacity and high CCA
- Long life
- •Advanced lead-calcium alloy technology, maintenance-free design
- •Patented venting system bring less water loss and prevent acid leakage
- •OE quality certification





Leoch International Technology Ltd.

mww.leoch.com

www.leoch.sg

Leoch Batteries Pte Ltd Leoch Battery Corporation

mww.leochamericas.com

Leoch Europe S.A.



GENERAL FEATURES

^{*}Values are subject to variation of +/- 5% in normal manufacturing processes.