FLOODED BATTERY 60D31R (12V65Ah)





CHARACTERISTICS


| Item | | Specifications |
|--------------------------------|--------|--------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity (20HR) | | 65Ah |
| Reserve Capacity | | 108min |
| Cold Cranking Amps@0°F (-18°C) | | 500A |
| | Length | 303mm (11.9inches) |
| Dimension | Width | 170mm (6.69inches) |
| | Height | 222mm (8.74inches) |
| Approx Weight | | 18.5kg (40.8lbs) |
| Terminal | | 1 |
| Cell layout | | 1 |
| Hold-Down | | B1 |
| Case | | Black-PP Material |
| Cover | | Black-PP Material |
| Handle | | TS1 |

APPLICATIONS

Car start

•EV/HEV

•Engine start



POS

NEG

+| 8

*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd. @ www.leoch.com

Leoch Batteries Pte Ltd www.leoch.sg

GENERAL FEATURES


•High capacity and high CCA


Long life

- •Advanced lead-calcium alloy technology, maintenance-free design
- •Patented venting system bring less water loss and prevent acid

leakage

•OE quality certification





Leoch Battery Corporation www.leochamericas.com

Leoch Europe S.A. @ www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-60D31R-PD-EN-V1.0-20241228