FLOODED BATTERY 80D26R (12V70Ah)





CHARACTERISTICS


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		70Ah
Reserve Capacity		118min
Cold Cranking Amps@0°F (-18°C)		600A
	Length	259mm (10.2inches)
Dimension	Width	174.8mm (6.88inches)
	Height	221mm (8.70inches)
Approx Weight		17.7kg (39.0lbs)
Terminal		1
Cell layout		1
Hold-Down		B1
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS1

APPLICATIONS

•Car start

•EV/HEV

•Engine start



POS



NEG

+| 8

*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd. www.leoch.com

Leoch Batteries Pte Ltd www.leoch.sg




•High capacity and high CCA

Long life


- •Advanced lead-calcium alloy technology, maintenance-free design
- •Patented venting system bring less water loss and prevent acid

leakage

•OE quality certification







Leoch Battery Corporation www.leochamericas.com

Leoch Europe S.A. 🛞 www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-80D26R-PD-EN-V1.0-20241228