




LEOCH BATTERY

# 6-QW-32(290)-L (12V32Ah)



## Dimensions (mm)




## Physical Specification (mm)

|                        |                             |                                     |
|------------------------|-----------------------------|-------------------------------------|
| Nominal Voltage        |                             | 12V                                 |
| Nominal Capacity(20HR) |                             | 32Ah                                |
| Dimension              | Length                      | 236±2mm(9.29inches)                 |
|                        | Width                       | 128±2mm(5.04inches)                 |
|                        | Container Height            | 200±2mm(7.87inches)                 |
|                        | Total Height(with Terminal) | 222±2mm(8.74inches)                 |
| Weight                 |                             | Approx 10.3Kg(22.71lbs)             |
| Acid                   |                             | 1.280±0.015g/cm <sup>3</sup> (25°C) |
| Standard Terminal      |                             | 3                                   |
| Cell layout            |                             | 0                                   |
| Hold-Down              |                             | B0                                  |
| Cell plate qty         |                             | /                                   |
| Case                   |                             | Black-PP Material                   |
| Cover                  |                             | Black-PP Material                   |
| Handle                 |                             | Black-PP Material                   |
| QTY/PLT/layer          |                             | /                                   |

## Electrical Specification

|   |                    |       |
|---|--------------------|-------|
| Rated Capacity                            | 20 hour rate(1.6A) | 32Ah  |
| Reserve Capacity                          |                    | 47min |
| Cold Cranking Performance Amps@0°F(-18°C) |                    | 290A  |

## Discharge Characteristics(25°C,70°F)




## Standard Terminal (mm)      Cell Layout

| Terminal Type | D                                 |                                   | Cell Layout Diagram |
|---------------|-----------------------------------|-----------------------------------|---------------------|
|               | Positive                          | Negative                          |                     |
| 3             | 14.7 <sup>0</sup> <sub>-0.3</sub> | 13.0 <sup>0</sup> <sub>-0.3</sub> |                     |

Figure(0)

## Discharge Characteristics(-18°C,0°F)



\*Values are subject to variation of +/- 5% in normal manufacturing processes.  
 \*Technical specifications and the product line above could be changed without prior notice.