
MAINTENANCE-FREE MOTORCYCLE BATTERY

EBX14L-BS(J) (12V12Ah)








CHARACTERISTICS

Item		Specifications
Nominal Voltage		12V
Nominal Capacity (10HR)		12Ah
Cold Cranking Performance Amps@0°F (-18°0		C) 160A
Dimension (±2mm)	Length	150mm (5.91inches)
	Width	87mm (3.43inches)
	Container Height	145mm (5.71inches)
	Total Height	145mm (5.71inches)
Battery (with acid)	Approx Weight	4.06kg (8.95lbs)
Electrolyte	Approx Weight	0.86kg (1.90lbs)
Terminal type		А
Battery type	Dry Charged Series	
Full Charge	Constant-Voltage Char	rge:
	Initial charging current	Less than 0.3C ₁₀
	Voltage	14.40V~15.00V at 25°C (77°F)
	Charging time	15~18h
	Constant-Current Char	rge:
	Charging current 0.1C ₁₀ , when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge	Initial charging current	Unlimited
	Voltage	13.50V~13.80V at 25°C (77°F)
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

GENERAL FEATURES

- Sealed AGM battery
- · Rest after filling acid
- Fresh Pack, Maintenance-Free



Leoch International Technology Ltd.

@ www.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.



^{*}Values are subject to variation of +/- 5% in normal manufacturing processes.