
## **MAINTENANCE-FREE MOTORCYCLE BATTERY**

LT4B-BS (12V2.3Ah)








## **GENERAL FEATURES**

- Sealed AGM battery
- · Rest after filling acid
- Fresh Pack, Maintenance-Free

## **CHARACTERISTICS**

	Specifications
	12V
OHR)	2.3Ah
mance Amps@0°F (-18°C)	30A
Length	113mm (4.45inches)
Width	38mm (1.50inches)
Container Height	85mm (3.35inches)
Total Height	85mm (3.35inches)
Approx Weight	0.92kg (2.03lbs)
Approx Weight	0.14kg (0.309lbs)
	J
Dry Charged Series	
Constant-Voltage Charge:	
Initial charging current	Less than 0.3C <sub>10</sub>
Voltage 14.4	40V~15.00V at 25°C (77°F)
Charging time	15~18h
Constant-Current Charge:	
Charging current 0.1C <sub>10</sub> , w 14.40V, continue to charge	hen charging voltage up to 4h
Initial charging current	Unlimited
Voltage 13.5	50V~13.80V at 25°C (77°F)
40°C (104°F)	106%
25°C (77°F)	100%
0°C (32°F)	86%
	mance Amps@0°F (-18°C)  Length  Width  Container Height  Total Height  Approx Weight  Approx Weight  Dry Charged Series  Constant-Voltage Charge: Initial charging current  Voltage 14.  Charging time  Constant-Current Charge: Charging current 0.1C₁0, w 14.40V, continue to charge Initial charging current  Voltage 13.  40°C (104°F)  25°C (77°F)



Leoch International Technology Ltd.

www.leoch.com

**Leoch Batteries Pte Ltd** 

www.leoch.sg

**Leoch Battery Corporation** 

www.leochamericas.com

Leoch Europe S.A.



<sup>\*</sup>Values are subject to variation of +/- 5% in normal manufacturing processes.