

MAINTENANCE-FREE MOTORCYCLE BATTERY


MX14-3-3 (12V13Ah)












GENERAL FEATURES

· Sealed and non-spillable AGM battery

· Shipped pre-charged and ready to install


· Maintenance-free



CHARACTERISTICS

Item		Specifications
Nominal Voltage		12V
Nominal Capacity (10HR)		13Ah
Cold Cranking Perfo	rmance Amps@0°F (-18	°C) 210A
Dimension (±2mm)	Length	150mm (5.91inches)
	Width	88.5mm (3.48inches)
	Container Height	145mm (5.71inches)
	Total Height	145mm (5.71inches)
Battery (with acid)	Approx Weight	4.55kg (10.0lbs)
Terminal type		Ν
Battery type	MX Series	
Full Charge	Constant-Voltage Charge:	
	Initial charging current	t Less than 0.3C10
	Voltage	14.40V~15.00V at 25°C (77°F)
	Charging time	15~18h
	Constant-Current Cha	irge:
	Charging current $0.1C_{10}$, when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge	Initial charging current	t Unlimited
	Voltage 13.50V~13.80V at 25°C (77°F)	
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

Discharge Characteristics (25°C, 77°F)



*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.

Leoch Batteries Pte Ltd

Leoch Battery Corporation www.leochamericas.com Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted. Subject to revisions without prior notice. E&OE.

Publication No.:LB-MX14-3-3-PD-EN-V1.0-20230710