
MAINTENANCE-FREE MOTORCYCLE BATTERY

MX15-3-1 (12V14Ah)







CHARACTERISTICS

Item		Specifications
Nominal Voltage		12V
Nominal Capacity (10HR)		14Ah
Cold Cranking Performance Amps@0°F (-18°C)		8°C) 240A
Dimension (±2mm)	Length	134mm (5.28inches)
	Width	89mm (3.50inches)
	Container Height	164mm (6.46inches)
	Total Height	164mm (6.46inches)
Battery (with acid)	Approx Weight	5.30kg (11.7lbs)
Terminal type		N
Battery type	MX Series	
Full Charge	Constant-Voltage Charge:	
	Initial charging curre	nt Less than 0.3C ₁₀
	Voltage	14.40V~15.00V at 25°C (77°F)
	Charging time	15~18h
	Constant-Current Ch	arge:
	Charging current $0.1C_{10}$, when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge	Initial charging curre	nt Unlimited
	Voltage	13.50V~13.80V at 25°C (77°F)
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%

Discharge Characteristics (25°C, 77°F)

Leoch International Technology Ltd.

www.leoch.sg

Leoch Batteries Pte Ltd

Leoch Battery Corporation

Leoch Europe S.A. www.leoch.eu



mww.leochamericas.com

^{12.0} **GENERAL FEATURES** Loading Voltage (V) · Maintenance-free · Sealed and non-spillable AGM battery 7.0 · Shipped pre-charged and ready to install 5 10 15 30 6023 10 20 min Discharge Time

^{*}Values are subject to variation of +/- 5% in normal manufacturing processes.