

深圳市迈科盛电源技术有限公司
Shenzhen Marxon Power Supply Co. Ltd.

FILE NO.:

VERSION NO.: A

DATE:

SPECIFICATION				
MODEL	LC5-36-5A	NAME	CLASS 2 BATTERY CHARGER	PHOTO 
PART NO.	LC-2157	SPEC.	36V 5A	
This charger is used for charging 36V Lead-Acid rechargeable battery only, other type of battery may burst causing injury to persons and damage.				
I	INPUT PROPERTY			
	1	AC input voltage range	90Vac~132Vac/185Vac~264Vac	Universal
	2	AC input voltage rating	100Vac~120Vac/200Vac~240Vac	
	3	AC input frequency	60Hz/50Hz	
	4	AC input current	4.5A @ 115Vac/2.3A @ 230Vac	Max. (RMS)
	5	AC input power	280W	Max.
	6	AC input static state current	0.1A	Max. (RMS)
	OUTPUT PROPERTY			
	1	Output voltage range	30-45.0Vdc	
	2	Output Current	5A @ 36Vdc	±5%
	3	Output power	225W	Max.
	4	Bulk charge current rating	5A	Typical
	5	Bulk charge voltage rating	44.1Vdc	±0.9Vdc
	6	Float charge voltage rating	41.0Vdc	±0.45Vdc
7	Light switching current	1.0A	±250mA	
II	GENERAL CHARACTERISTICS			
	1	Efficiency	80% (Typical)	At Max. Load
	2	Over load protection	<8A	
	3	Short circuit protection	Enable	
	4	Reversed polarity connectors protection	Enable	
	5	Operating temperature	0°C~40°C	
	6	Storage temperature	-30°C~85°C	
	7	Operating relative humidity	8%~90%	
	8	Storage relative humidity	5%~95%	
III	INDICATOR STATUS			
	1	Red LED on	Power on	
	2	Orange LED on	Bulking charge	
	3	Green LED on	Floating charge or empty load	
	4			
	5			

PREPARED BY:

CHECKED BY:

APPROVED BY:

深圳市迈科盛电源技术有限公司
Shenzhen Marxon Power Supply Co. Ltd.

FILE NO.:

VERSION NO.: A

DATE:

SPECIFICATION					
MODEL	LC5-36-5A	NAME	CLASS 2 BATTERY CHARGER	SPEC.	36V 5A
V	SAFETY				
	1	Withstand Voltage (Hi-Pot)	3000Vac 10mA (60 Sec.)	I/p to O/p	
	2	Insulation resistance	More than 100MΩ at 500Vdc	25°C & 70%RH	
	3	Temperature Rise	<75°C	Enclosure	
	4	Safety Standard	Designed to meet UL1012/CSA		
	5	EMI/RFI Standard	Designed to meet CE Class B	EN55022-B	
IV	RELIABILITY				
	1	Spot test	Burn in 24 hours at 40°C	Full load	
	2	Whole test	Burn in 2hour at 40°C	Full load	
	3				
VI	MECHANICAL CHARACTERISTICS				
	1	Net Weight	1.5Kg		
	2	Dimension	208mm×130mm×82mm	L×W×H	
	3	Enclosure	Metal case		
VII	CHARGE CHARACTERISTICS				
	<p style="text-align: center;"> Charge current (A) Charge voltage (V) 5A Voltage 44.1V 1.0A Current 41.0V 0A 30V 0V Constant current Constant voltage Float charge </p>				

PREPARED BY:

CHECKED BY:

APPROVED BY: