

深圳市迈科盛电源技术有限公司
Shenzhen Marxon Power Supply Co. Ltd.

FILE NO.:

VERSION NO.:

DATE:

SPECIFICATION					
MODEL	LC-2205	NAME	Class 2 battery charger	PHOTO	
PART NO.		SPEC.	12V 800mA		
Switch Power Supply; For 12V lead-acid battery only.					
INPUT PROPERTY					
I	1	AC input voltage range	90Vac~264Vac	Universal	
	2	AC input voltage rating	100Vac~240Vac		
	3	AC input frequency	47Hz~63Hz		
	4	AC input current	0.23A@115Vac/0.15A@230Vac	Max. (RMS)	
	5	AC input power	17.5W	Max.	
	6	AC input static state current	30mA	Max.	
	OUTPUT PROPERTY				
	1	Output voltage range	10~15Vdc		
	2	Output Current	800mA@12Vdc	±10%	
	3	Output power	11.5W	Max.	
	4	Bulk charge current rating	800mA	Typical	
	5	Bulk charge voltage rating	14.7Vdc	±0.3Vdc	
	6	Float charge voltage rating	13.65Vdc	±0.15Vdc	
	7	Light switching current	160mA	±40mA	
GENERAL CHARACTERISTICS					
II	1	Efficiency	66%	Typical	
	2	Over load protection	<1.2 A		
	3	Short circuit protection	Enable		
	4	Reversed polarity connectors protection	Enable		
	5	Operating temperature	0°C~40°C		
	6	Storage temperature	-30°C~85°C		
	7	Operating relative humidity	8%~90%		
	8	Storage relative humidity	5%~95%		
INDICATOR STATUS					
III	1	Green LED on	Empty load or float charge		
	2	Red LED on	Bulk charge		
	3				
	4				
	5				



PREPARED BY:

CHECKED BY:

APPROVED BY:

深圳市迈科盛电源技术有限公司
Shenzhen Marxon Power Supply Co. Ltd.

FILE NO.:

VERSION NO.:

DATE:

SPECIFICATION					
MODEL	LC-2205	NAME	Class 2 battery charger	SPEC.	12V 800mA
IV	SAFETY				
	1	Withstand Voltage (Hi-Pot)	3750Vac ≤10mA (60s)		I/P to O/P
	2	Insulation Resistance	>100MΩ @500Vdc		25°C & 70%RH
	3	Temperature Rise	<75°C		Case
	4	Safety Standard	UL1310 (E248494)		
	5	EMI/RFI Standard	Designed to meet EN55022-B		
VI	RELIABILITY				
	1	Spot test	Burn in 24h at 40°C		Full load
	2	Whole test	Burn in 1h at 40°C		Full load
VII	MECHANICAL CHARACTERISTICS				
	1	Net Weight	205g		
	2	Dimension	82mm*57mm*45mm		L×W×H
VIII	CHARGE CHARACTERISTICS				
	<p style="text-align: center;"> Charge current (A) Charge voltage (V) </p> <p style="text-align: center;"> 800mA 14.7V </p> <p style="text-align: center;"> 160mA 13.65V </p> <p style="text-align: center;"> 0A 10V </p> <p style="text-align: center;"> 0V </p> <p style="text-align: center;"> Constant current Constant voltage Float charge </p>				

PREPARED BY:

CHECKED BY:

APPROVED BY: