




LPL Series-Long Life Standby

LPL2-150(2V150Ah)




Specifications

Rated Voltage	2V	
Nominal Capacity	150.0Ah	(C ₁₀ , 1.80V/cell)
Dimension	Length	170±2mm (6.69 inches)
	Width	98±1mm (3.86 inches)
	Container Height	205±3mm (8.07 inches)
	Total Height	214±3mm (8.42 inches)
Approx Weight	8.5 Kg (18.7 lbs)	
Terminal	M6	
Container Material	ABS or PP	
Rated Capacity (25°C)	160.0 Ah	(20hr, 8.00A, 1.80V/cell)
	150.0 Ah	(10hr, 15.0A, 1.80V/cell)
	133.0 Ah	(5hr, 26.6A, 1.75V/cell)
	115.8 Ah	(3hr, 38.6A, 1.75V/cell)
	90.1 Ah	(1hr, 90.1A, 1.60V/cell)
Max. Discharge Current	1200A (5s)	
Internal Resistance (25°C)	Approx 1.1mΩ	
Operating Temp. Range	Discharge	-15 ~ 50°C (5 ~ 122°F)
	Charge	0 ~ 40°C (32 ~ 104°F)
	Storage	-15 ~ 40°C (5 ~ 104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than 45.0A. Voltage	
	2.4V~2.5V at 25°C(77°F)Temp. Coefficient -5mV/°C	
Standby Use	Initial Charging Current less than 45.0A. Voltage	
	2.25V~2.30V at 25°C(77°F)Temp. Coefficient -3mV/°C	
Effect of temp. to Capacity	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	LPL series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Layout



Constant Current Discharge (Amperes) at 25 °C (77°F)


F.V/Time	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	150.9	135.9	112.6	90.2	75.2	46.7	35.6	29.1	24.8	21.6	17.3	14.4	7.73
1.80V/cell	171.5	151.4	120.8	94.9	78.7	48.8	37.4	30.4	25.8	22.6	18.1	15.0	8.00
1.75V/cell	188.4	163.2	127.9	99.8	82.1	50.7	38.6	31.4	26.6	23.2	18.4	15.2	8.04
1.70V/cell	201.2	174.6	134.2	103.6	85.0	52.7	39.8	32.1	27.1	23.6	18.8	15.4	8.13
1.65V/cell	212.0	183.2	140.8	108.1	88.0	54.5	40.7	32.8	27.7	24.0	19.0	15.6	8.21
1.60V/cell	222.2	189.9	145.6	111.0	90.1	55.5	41.4	33.3	28.1	24.3	19.3	15.8	8.27

Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	285.7	258.5	215.1	173.5	145.5	90.7	69.6	57.1	48.8	42.8	34.4	28.7	15.4
1.80V/cell	320.5	284.9	228.9	181.3	151.3	94.4	72.6	59.4	50.7	44.5	35.8	29.8	15.9
1.75V/cell	347.2	303.5	240.6	189.6	157.2	97.8	74.9	61.2	52.0	45.4	36.4	30.1	16.0
1.70V/cell	366.9	322.0	250.3	195.3	161.9	101.2	76.9	62.3	52.8	46.2	37.0	30.5	16.1
1.65V/cell	381.8	334.2	260.6	202.7	166.7	104.1	78.3	63.5	53.7	46.8	37.4	30.8	16.3
1.60V/cell	393.6	342.6	266.9	206.2	169.5	105.5	79.2	64.1	54.3	47.3	37.9	31.2	16.4



LPL Series-Long Life Standby LPL2-150(2V150Ah)



Applications

- Tele-communication central station (wired or cellular)
- Power system communication, military communication, etc.
- Network communication including: data transmission, television signal transmission, etc.
- Uninterruptable Power System (UPS- for Telecom)
- EPS


General Features

- 20 years design life
- Grid refining technology and the thicker plates are used to extend the battery standby life and reduce the plate grid corrosion speed
- Using oxygen recombination technology: maintenance-free
- Unique vent valve design: control water losing, prevent air and spark going inside
- Can be operated in upright, side, or end mounting orientation


Standards

- Compliance with IEC 60896 standards, EU Battery Directive
- UL, CE Certified
- Manufactured in Leoch® IATF 16949, OHSAS 18001, ISO 9001 and ISO 14001 certified production facilities


Discharge Characteristics




Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Design Life



Sales Offices Worldwide

China Sales Office

5th Floor, Xinbaohui Bldg., Nanhai Blvd.,
Nanshan, Shenzhen, China. 518052
Tel: +86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail: export@leoch.com

North America Sales Office

19751 Descartes
Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us

HongKong Sales Office

Workshop C, 33/F, TML Tower, No. 3 Hoi Shing Road,
Tsuen Wan, New Territories, Hong Kong
Tel: +852 35786666
Fax: +44 1452 690125
E-mail: sales.hk@leoch.com

UK Sales Office

9B Wheatstone Court, Waterwells, Business Park,
Gloucester, GL2-2AQ, UK United Kingdom
Tel: +44(0) 1452 729428 / 1452 729696
Fax: +44 1452 690125
E-mail: Sales.Europe@leoch.com

Singapore Sales Office

No. 1 Tech Park Crescent,
Singapore 638131
Tel: +65 68636078
Fax: +65 6863 6079
Email: sales.sg@leoch.com

EMEA Sales Office

1 Deligiorgi St., 121 31 Athens,
Greece
Tel: +30 210 5760318 (2 lines)
E-mail: support_EMEA@leoch.com

Australia Sales Office

2/29 Tarlington Place, Smithfield. NSW 2164
Australia
Tel: 02 9756 0950
E-mail: sales.au@leoch.com

India Sales Office

Shed no.A-53(b), 2nd Stage of Peenya Industrial Area,
Bangalore North Taluk, Bangalore-560058, India
Tel: +91-80-23440018/23440019
Fax: +91-80-23440017
E-mail: indiasales@leoch.com



[Http://www.leoch.com](http://www.leoch.com)

[Http://www.leoch.us](http://www.leoch.us)

© 2018 LEOCH. All rights reserved.

Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.
Subject to revisions without prior notice.

Publication No.: LP-LPL2-150-SGTHSE-V2.1-201909