



# DEEP CYCLE



## LDC8-180-GC8

### FEATURES&BENEFITS

- True deep cycle AGM-GEL technology-GREEN SOLUTION
- Over 99.99% virgin lead for grid plate
- Carbon active material
- Electrolyte + Gel for longer cycle life
- Heavy duty grid/paste design for deep cycle application
- Maintenance free, non-spillable, valve-regulated
- Double separator configuration :long cycle life &High energy density and super anti-vibration design
- Low self-discharge for longer shelf life



### ELECTRICAL SPECIFICATIONS

Voltage (V)	Capacity(Ah)					Reserve Capacity(min)		
	100HR	20HR	10HR	5HR	3HR	25A	56A	75A
8	200	182	170	153	135	365	155	/

### PHYSICAL SPECIFICATIONS

Dimensions(mm/inches)				Weight (kg/lbs)	Terminal Type (Standard)	Case Material
Length	Width	Height	Total Height			
260/10.24	180/7.09	252/9.92	274/10.79	30.8/67.9	DT(5/16")	PP

Operating Temperature Range		
Discharge	Charge	Storage
-20°C~55°C(-4°F~131°F)	0C~40°C(32°F-104°F)	-15°C~40°C(5°F~104°F)




IATF16949

ISO14001

ISO9001

# LDC8-180-GC8


## DIMENSIONS




Note: D: Positive  $19.5_{-0.3}^0$ , D: Negative  $17.9_{-0.3}^0$ ; Terminal Torque Values in-lb(Nm): 176-203(20-23)

## PERFORMANCE CHARACTERISTICS


Charging Profile




Relationship of OCV and State Of Charge ( $25^{\circ}C, 77^{\circ}F$ )



Cycle Life in Relation to Depth Of Discharge



Self-discharge Characteristic



### LEOCH INTERNATIONAL SALES OFFICE:

Add: 14th Floor, Block A, Building 6,  
Zhonggang Plaza, Exhibition Bay, Shenzhen, China.  
Tel: +86-755-86036060 (100 lines)  
E-mail: export@leoch.com  
web: www.leoch.com

DEEP CYCLE AGM-GEL BATTERY