



# LPC SERIES-CYCLE APPLICATION

## LPC12-100 (12V100Ah)



### CHARACTERISTICS

Item	Specifications	
Voltage	12V	
Dimension	Length	330mm (13.0inches)
	Width	173mm (6.81inches)
	Container Height	212mm (8.35inches)
	Total Height	220mm (8.66inches)
Approx Weight	30.6kg (67.5lbs)	
Terminal	T11(M8)	
Container Material	ABS	
Short-circuit current	2000A	
Internal Resistance (25°C)	≤ 4.9 mΩ	
Self Discharge	≤3% per month at 25°C (77°F)	
Capacity	20HR	105Ah
	10HR	100Ah
	5HR	91Ah
Operating Temp.Range	Discharge	-20~55°C (-4~131°F)
	Charge	0~40°C (32~104°F)
	Storage	-20~50°C (-4~122°F)



### APPLICATIONS

- Golf trolley
- Medical facility
- Mobility scooter
- Electric wheelchair
- Other mobility device

### STANDARDS

- ACC. to BCI standards
- Manufactured in Leoch® IATF16949, ISO 9001, ISO 14001 and ISO 45001 certified production facilities


# LPC SERIES-CYCLE APPLICATION

## LPC12-100 (12V100Ah)


### GENERAL FEATURES

- Good cyclic property: Enhanced overcharge endurance and overdischarge recovery property
- Using oxygen recombination technology: maintenance-free
- Lower acid density, excess of electrolyte and larger distance between plates to keep battery at low temperature and slow down plate grid corrosion speed
- Unique plate group configuration, high quality AGM separator and battery management system ensure battery with a longer service life


#### Discharge Characteristics



#### Charging Characteristics



#### Cycle Life in Relation to Depth of Discharge



#### Self Discharge Characteristics

