




LP Series-General Purpose LP2-65(2V65Ah)




Specifications

Rated Voltage	2V	
Nominal Capacity	65.0Ah	(C ₁₀ , 1.80V/cell)
Dimension	Length	170±2mm (6.69 inches)
	Width	72±2mm (2.83 inches)
	Container Height	205±2mm (8.07 inches)
	Total Height	214±2mm (8.43 inches)
Approx Weight	4.2 Kg (9.26 lbs)	
Terminal	T6(M6)	
Container Material	ABS	
Rated Capacity (25°C)	68.2 Ah	(20hr, 3.41A, 1.80V/cell)
	65.0 Ah	(10hr, 6.50A, 1.80V/cell)
	57.5 Ah	(5hr, 11.5A, 1.75V/cell)
	49.5 Ah	(3hr, 16.5A, 1.75V/cell)
	41.6 Ah	(1hr, 41.6A, 1.60V/cell)
Max. Discharge Current	520A (5s)	
Internal Resistance (25°C)	Approx 1.2mΩ	
Operating Temp. Range	Discharge	-15 ~ 50°C (5 ~ 122°F)
	Charge	-20 ~ 40°C (-4 ~ 104°F)
	Storage	-15 ~ 40°C (5 ~ 104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Standby Use	Initial Charging Current less than 19.5A. Voltage 2.25V~2.30V at 25°C(77°F)Temp. Coefficient -3mV/°C	
	Initial Charging Current less than 19.5A. Voltage 2.40V~2.50V at 25°C(77°F)Temp. Coefficient -5mV/°C	
Effect of temp. to Capacity	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	LP series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Layout



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	75.0	59.0	53.1	40.3	33.8	22.8	19.3	15.3	12.5	10.7	9.63	7.53	6.04	3.17
1.80V/cell	85.0	66.7	59.2	42.7	35.8	24.1	20.3	16.3	13.1	11.1	10.0	7.72	6.50	3.41
1.75V/cell	92.1	72.0	61.8	44.2	38.0	25.5	21.2	16.5	13.6	11.5	10.3	7.85	6.56	3.45
1.70V/cell	97.8	76.4	62.5	45.1	39.7	26.7	22.0	17.1	13.9	11.6	10.4	7.98	6.63	3.48
1.67V/cell	100.6	78.5	63.5	45.8	41.1	27.6	22.7	17.6	14.2	11.8	10.6	8.11	6.69	3.51
1.60V/cell	103.7	80.5	64.4	46.4	41.6	28.3	23.0	17.9	14.4	12.0	10.7	8.17	6.76	3.55

Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	142.1	112.2	97.3	77.5	54.3	41.4	34.1	26.0	21.4	19.6	17.3	12.9	10.8	5.66
1.80V/cell	158.9	125.6	108.5	81.6	58.4	44.6	36.8	27.8	22.6	20.7	18.2	13.3	11.0	5.75
1.75V/cell	169.6	134.0	113.2	84.0	61.4	46.6	38.2	28.7	23.3	21.4	18.7	13.5	11.1	5.82
1.70V/cell	178.3	140.9	114.6	85.1	64.2	48.2	39.2	29.5	24.0	21.8	19.1	13.6	11.2	5.88
1.67V/cell	181.2	143.2	116.4	85.8	67.0	49.9	40.3	30.4	24.6	22.0	19.3	13.7	11.3	5.95
1.60V/cell	183.8	145.2	118.2	86.3	69.7	51.4	41.1	31.0	24.9	22.4	19.6	14.0	11.5	6.05



LP Series-General Purpose LP2-65(2V65Ah)



Applications

- Tele-communication central station (wired or cellular)
- Power system communication, military communication, etc.
- Network communication including: data transmission, television signal transmission, etc.
- Uninterruptable Power System (UPS- for Telecom)


General Features

- 15 years design life(25°C)
- Special exhaust structure and sealing technology, safe and reliable, flexible installation, convenient maintenance
- PbCaSn alloy for plate grids: less gassing, less self-discharging
- High quality AGM separator: extend cycle life and prevent micro short circuit
- High purity raw material: ensure low self discharge rate


Standards

- Compliance with IEC 60896 standards, EU Battery Directive
- UL, CE Certified
- Manufactured in Leoch®IATF16949, ISO45001,ISO 9001 and ISO 14001 certified production facilities


Discharge Characteristics




Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Effect of Temperature on Long Term Float Life



Sales Offices Worldwide

China Sales Office

5th Floor, Xinbaohui Bldg., Nanhai Blvd.,
Nanshan, Shenzhen, China. 518052
Tel: +86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail: export@leoch.com

HongKong Sales Office

Workshop C, 33/F, TML Tower, No. 3 Hoi Shing Road,
Tsuen Wan, New Territories, Hong Kong
Tel: +852 35786666
Fax: +44 1452 690125
E-mail: sales.hk@leoch.com

Singapore Sales Office

No. 1 Tech Park Crescent,
Singapore 638131
Tel: +65 68636078
Fax: +65 6863 6079
Email: sales.sg@leoch.com

Australia Sales Office

2 /29 Tarlington Place, Smithfield, NSW 2164
Australia
Tel: 02 9756 0950
E-mail: sales.au@leoch.com

North America Sales Office

19751 Descartes
Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us
Http:// www.leoch.us

UK Sales Office

9B Wheatstone Court, Waterwells, Business Park,
Gloucester, GL2-2AQ, UK United Kingdom
Tel: +44(0) 1452 729428 / 1452 729696
Fax: +44 1452 690125
E-mail: Sales.Europe@leoch.com
Http:// www.leoch.eu

EMEA Sales Office

1 Deligiorgi St., 121 31 Athens,
Greece
Tel: +30 210 5760318 (2 lines)
E-mail: support_EMEA@leoch.com
Http:// www.leoch.eu

India Sales Office

Shed no.A-53(b), 2nd Stage of Peenya Industrial Area,
Bangalore North Taluk, Bangalore-560058, India
Tel: +91-80-23440018/23440019
Fax: +91-80-23440017
E-mail: indiasales@leoch.com



[Http://www.leoch.com](http://www.leoch.com)

© 2022 LEOCH. All rights reserved.

Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.
Subject to revisions without prior notice.

Publication No.: LB-LP2-65-PD-EN-V2.2-202211