FLOODED HIGH TEMPERATURE BATTERY 40B24RHT (12V40Ah)





CHARACTERISTICS


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		40Ah
Reserve Capacity		61min
Cold Cranking Amps@0°F (-18°C)		350A
Dimension	Length	236mm (9.29inches)
	Width	128mm (5.04inches)
	Height	222mm (8.74inches)
Approx Weight		11.2kg (24.7lbs)
Terminal		3
Cell layout		1
Hold-Down		B0
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS1


APPLICATIONS

•Car start

•EV/HEV


•Engine start






GENERAL FEATURES

- •Design for high temperature countries and regions
- •Superior life in high temperature environment
- •High tin alloy and thicker positive grid
- •High-temp paste
- •Patented venting system bring less water loss and prevent acid leakage







*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.

Leoch Batteries Pte Ltd

Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-40B24RHT-PD-EN-V1.0-20250103