FLOODED HIGH TEMPERATURE BATTERY

46B24LHT (12V45Ah)





CHARACTERISTICS


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		45Ah
Reserve Capacity		70min
Cold Cranking Amps@0°F (-18°C)		350A
	Length	236mm (9.29inches)
Dimension	Width	128mm (5.04inches)
	Height	222mm (8.74inches)
Approx Weight		11.7kg (25.8lbs)
Terminal		3
Cell layout		0
Hold-Down		В0
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS1

APPLICATIONS


- Car start
- •EV/HEV
- •Engine start

Ø 14. 7 \(\frac{0}{0} \) 3 \\ \frac{11}{11} \\ \frac{1}{11} \

- •Design for high temperature countries and regions
- ·Superior life in high temperature environment
- ·High tin alloy and thicker positive grid
- ·High-temp paste
- Patented venting system bring less water loss and prevent acid leakage







Leoch International Technology Ltd.

mww.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.



GENERAL FEATURES

^{*}Values are subject to variation of +/- 5% in normal manufacturing processes.