## FLOODED HIGH TEMPERATURE BATTERY

## 55530HT (12V55Ah)





## **CHARACTERISTICS**


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		55Ah
Reserve Capacity		88min
Cold Cranking Amps@0°F (-18°C)		420A
	Length	242mm (9.53inches)
Dimension	Width	175mm (6.89inches)
	Height	190mm (7.48inches)
Approx Weight		14.4kg (31.7lbs)
Terminal		1
Cell layout		0
Hold-Down		B13
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS2

## **APPLICATIONS**

•Car start

•EV/HEV


•Engine start



\*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.

Leoch Batteries Pte Ltd



**GENERAL FEATURES** 

·High tin alloy and thicker positive grid

•High-temp paste


leakage

·Design for high temperature countries and regions

·Patented venting system bring less water loss and prevent acid

•Superior life in high temperature environment





Leoch Battery Corporation

Leoch Europe S.A.

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-55530HT-PD-EN-V1.0-20250103