FLOODED HIGH TEMPERATURE BATTERY

56221HT (12V60Ah)





CHARACTERISTICS


| Item | | Specifications |
|--------------------------------|--------|--------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity (20HR) | | 60Ah |
| Reserve Capacity | | 98min |
| Cold Cranking Amps@0°F (-18°C) | | 470A |
| | Length | 242mm (9.53inches) |
| Dimension | Width | 175mm (6.89inches) |
| | Height | 190mm (7.48inches) |
| Approx Weight | | 15.0kg (33.1lbs) |
| Terminal | | 1 |
| Cell layout | | 1 |
| Hold-Down | | B13 |
| Case | | Black-PP Material |
| Cover | | Black-PP Material |
| Handle | | TS2 |
| | | |

APPLICATIONS

- ·Car start
- •EV/HEV
- •Engine start

GENERAL FEATURES

- •Design for high temperature countries and regions
- •Superior life in high temperature environment
- ·High tin alloy and thicker positive grid
- •High-temp paste
- •Patented venting system bring less water loss and prevent acid leakage



Leoch International Technology Ltd.

@ www.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.



^{*}Values are subject to variation of +/- 5% in normal manufacturing processes.