FLOODED HIGH TEMPERATURE BATTERY

57539HT (12V75Ah)





CHARACTERISTICS


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		75Ah
Reserve Capacity		128min
Cold Cranking Amps@0°F (-18°C)		540A
	Length	314mm (12.4inches)
Dimension	Width	174mm (6.85inches)
	Height	174mm (6.85inches)
Approx Weight		18.3kg (40.3lbs)
Terminal		1
Cell layout		0
Hold-Down		B13
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS6

APPLICATIONS

•Car start


•EV/HEV

•Engine start




GENERAL FEATURES

- ·Design for high temperature countries and regions
- •Superior life in high temperature environment
- •High tin alloy and thicker positive grid
- •High-temp paste
- •Patented venting system bring less water loss and prevent acid leakage







Leoch Europe S.A.

*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd.

Leoch Batteries Pte Ltd

Leoch Battery Corporation

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved. Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-57539HT-PD-EN-V1.0-20250103