FLOODED HIGH TEMPERATURE BATTERY 61042HT (12V110Ah)





CHARACTERISTICS


Item		Specifications
Nominal Voltage		12V
Nominal Capacity (20HR)		110Ah
Reserve Capacity		201min
Cold Cranking Amps@0°F (-18°C)		780A
	Length	394mm (15.5inches)
Dimension	Width	175mm (6.89inches)
	Height	190mm (7.48inches)
Approx Weight		25.5kg (56.2lbs)
Terminal		1
Cell layout		0
Hold-Down		B13
Case		Black-PP Material
Cover		Black-PP Material
Handle		TS6

APPLICATIONS

Car start


•EV/HEV


•Engine start




GENERAL FEATURES

- ·Design for high temperature countries and regions
- •Superior life in high temperature environment
- ·High tin alloy and thicker positive grid
- •High-temp paste
- ·Patented venting system bring less water loss and prevent acid leakage







*Values are subject to variation of +/- 5% in normal manufacturing processes.

Leoch International Technology Ltd. www.leoch.com

Leoch Batteries Pte Ltd www.leoch.sg

Leoch Battery Corporation www.leochamericas.com

Leoch Europe S.A. @ www.leoch.eu

Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation. © LEOCH. All rights reserved.Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.

Publication No.:LB-61042HT-PD-EN-V1.0-20250103