


MAINTENANCE-FREE MOTORCYCLE BATTERY

HPGMX30-3-P (12V32Ah)



GENERAL FEATURES


- Maintenance-free
- Sealed and non-spillable AGM battery
- Shipped pre-charged and ready to install

*Values are subject to variation of +/- 5% in normal manufacturing processes.

CHARACTERISTICS

Item	Specifications
Nominal Voltage	12V
Nominal Capacity (10HR)	32Ah
Cold Cranking Performance Amps@0°F (-18°C)	480A
Dimension (±2mm)	Length 170mm (6.69inches)
	Width 132.5mm (5.22inches)
	Container Height 175mm (6.89inches)
	Total Height 175mm (6.89inches)
Battery (with acid)	Approx Weight 10.47kg (23.1lbs)
Terminal type	R
Battery type	HPG Series
Voltage Full Charge	Constant-Voltage Charge:
	Initial charging current Less than 0.3C ₁₀
	14.40V~15.00V at 25°C (77°F)
	Charging time 15~18h
	Constant-Current Charge:
	Charging current 0.1C ₁₀ , when charging voltage up to 14.40V, continue to charge 4h
Floating Charge Voltage	Initial charging current Unlimited
	13.50V~13.80V at 25°C (77°F)
Capacity affected by Temperature	40°C (104°F) 106%
	25°C (77°F) 100%
	0°C (32°F) 86%
	-15°C (5°F) 65%

Discharge Characteristics (25°C, 77°F)



Leoch International Technology Ltd.

www.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.

www.leoch.eu