


## Starter batteries for motorcycles LFPS-X9 [12.8V3Ah]

### **Physical Specification**

Nominal Voltage		12.8V	
Nominal Capacity		3.0Ah	
Dimension	Length	150±2mm (5.91 inches)	
	Width	$87\pm2\text{mm}$ (3.43 inches)	
	Container Height	105±2mm (4.13 inches)	
	Total Height (with Terminal)	105±2mm (4.13 inches)	
Weight	Approx 0.67kg (1.48lbs)		



150.0±2

- \* Motorcycle Li-ion battery
- \* Powerful 210 cranking amps
- \* Shipped pre-charged and ready to install
- \* Built in BMS to monitor the battery status in real time and protect the battery
- \* Replaces YTX9-BS/YTR9-BS battery

### **Dimensions (mm)**

### **Electrical Specification**

Rated Capacity	0.1C rate (0.3A)	3.0Ah
	0.5C rate (1.5A)	3.0Ah
	10C rate (30.0A)	2.7Ah
	70C rate (210.0A)	Peak Current
Capacity affected by Temperature	40 °C (104 °F)	98%
	25 °C (77 °F)	100%
	0 °C (32 °F)	85%
	-20 °C (-4 °F)	60%
Self	Approximately 1.5% per month	
Discharge	(25°C (77°F))	
Charging Methods	Constant-Voltage Charge:	
	Full Charge Initial charging current: less than 1.5A	
	Voltage: 14.40 V ~ 14.60 V at 25 °C (77 °F)	



# Discharge Characteristics (25°C,77 °F ) 14.5 14.5 13.5 13.0 13.0 13.0 13.0 13.0 13.0 13.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10.0 1

## Cycle life (1C,25°C,77°F) 120% 110% 90% 80% 70% 60%

500

Cycles

Publication No :LB-LFPS-X9-PD-EN-V1.3-202112

600 700 800

**Curve Specification** 

© 2021 LEOCH. All rights reserved.

Trademarks and logos are the property of
LEOCH and its affiliates unless otherwise noted.

Subject to revisions without prior notice.

0

100 200 300 400

Capacity (%)



900 1000