





MAINTENANCE-FREE MOTORCYCLE BATTERY

EB30A-4 (12V30Ah)



GENERAL FEATURES


- Maintenance-free
- Sealed and non-spillable AGM battery
- Shipped pre-charged and ready to install

*Values are subject to variation of +/- 5% in normal manufacturing processes.

CHARACTERISTICS

Item	Specifications
Nominal Voltage	12V
Nominal Capacity (10HR)	30Ah
Cold Cranking Performance Amps @0°F (-18°C)	325A
Dimension (±2mm)	Length 184mm (7.24inches) Width 124mm (4.88inches) Container Height 170mm (6.69inches) Total Height 170mm (6.69inches)
Battery (with acid)	Approx Weight 9kg (19.8lbs)
Terminal type	G
Battery type	Factory Activated Series
Constant-Voltage Charge:	
Initial charging current Less than 0.3C ₁₀	
Voltage 14.40V~15.00V at 25°C (77°F)	
Charging time 15~18h	
Constant-Current Charge:	
Charging current 0.1C ₁₀ , when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge	
Initial charging current Unlimited	
Voltage 13.50V~13.80V at 25°C (77°F)	
40°C (104°F) 106%	
25°C (77°F) 100%	
0°C (32°F) 86%	
-15°C (5°F) 65%	

Discharge Characteristics (25°C, 77°F)



Leoch International Technology Ltd.

www.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

www.leoch.us

Leoch Europe S.A.

www.leoch.eu