


MAINTENANCE-FREE MOTORCYCLE BATTERY

EBC14C-4-P (12V14Ah)



GENERAL FEATURES


- Maintenance-free
- Sealed and non-spillable AGM battery
- Shipped pre-charged and ready to install

*Values are subject to variation of +/- 5% in normal manufacturing processes.

CHARACTERISTICS

| Item | Specifications |
|---|--|
| Nominal Voltage | 12V |
| Nominal Capacity (10HR) | 14Ah |
| Cold Cranking Performance Amps@0°F (-18°C) | 200A |
| Dimension (±2mm) | Length 150mm (5.91inches) Width 87mm (3.43inches) Container Height 145mm (5.71inches) Total Height 145mm (5.71inches) |
| Battery (with acid) | Approx Weight 4.28kg (9.43lbs) |
| Terminal type | A |
| Battery type | Factory Activated Series |
| Constant-Voltage Charge: | |
| Initial charging current Less than 0.3C ₁₀ | |
| Full Charge | Voltage 14.40V~15.00V at 25°C (77°F) Charging time 15~18h |
| Constant-Current Charge: | |
| Charging current 0.1C ₁₀ , when charging voltage up to 14.40V, continue to charge 4h | |
| Floating Charge | Initial charging current Unlimited Voltage 13.50V~13.80V at 25°C (77°F) |
| 40°C (104°F) 106% | |
| Capacity affected by Temperature | 25°C (77°F) 100% 0°C (32°F) 86% -15°C (5°F) 65% |

Discharge Characteristics (25°C, 77°F)



Leoch International Technology Ltd.

www.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.

www.leoch.eu