## **Residential Energy Storage System** (Low Voltage & Stackable)



RS-LBS51.2-300-W



## **Product Information**



Self-Consumption Optimization 191



Maximum flexibility for any applications with up to 12

modules connected in parallel



Integrated with inverter to avoid the compatibility

4	
Ы	

LFP battery, safety and long cycle life

Stackable design, effortlessly installation



Capable of High-Powered Emergency-Backup and Off-Grid Function

## [4] Battery Module

- 5.12 kWh per Module
- · Modular and Stack Installation Design to simplify the maintenance
- · Connect up to 12 module in parallel for a maximum size of 60 kWh



## Flexible, Efficient, Simple



4		

High Power Power for Every Application

Technical Parameters			
Inverter	LBS 5.6KW Inverter-W		
Rated Power	5600W		
Maximum PV Array Open Circuit voltage	500VDC		
MPPT Voltage Range	120-450V		
Nomial Output Voltage	220/230/240VAC		
Output Voltage Range	184-265VAC		
Nominal Output Current	25.5A/24.3A/23.3A		
Efficiency	Up to 93.5%		
Grid Output Voltage Range	120-280VAC		
Grid Frequency	50/60Hz(Auto Sensing)		
Maximum AC Charge Current	120A		
Maximum Solar Charge Current	120A		
Nominal DC Voltage	48VDC		
Battery Model	LBS51.2-300S-W		
Combination Method	16S1P		
Deted Conseits	Typical	300Ah	
Rated Capacity	Minimum	296Ah	
Rated Voltage	51.2V		
Limited Discharge Voltage	43.2V		
Limited Charge Voltage	57.6V		
Internal Resistance(single battery pack)	≤20mΩ		
Max Continuous Charging Current	100A		
Max Continuous Discharging Current	100A		
Operation Temperature Range	Charge:0~50 ℃/ Discharge: -10~50 ℃		
Storage Temperature Range	0~50 °C,Recommend: ≤60±25%RH storage humidity		
Single Module Size/weight	680*429*215mm /50Kg±1Kg		
-	680*429*980mm /185Kg±1Kg		